

EAGLE SERIES - FIRE ALARM SYSTEMS

EXPLOSION PROOF MANUAL PULL STATION

LE-HPS-SA-EX/WP

DESCRIPTION

The Lifeco LE-HPS-SA-EX/WP Explosion Proof Manual Pull Station is a single action, UL listed fire alarm initiating device. With a UL rating of class I groups B (hydrogen), C and D; class II groups E, F and G; class III and an outdoor rating of type 4X, this station offers unmatched placement flexibility. The 2 sets of Form "C" (NO/C/NC) contacts are rated for 10 Amps at 120/ 240 VAC. The LE-HPS-SA-EX/WP has an easily identifiable pull down lever and contains an integral break glass rod carrier.

The unit is a high quality manual fire alarm box constructed entirely of a high strength metal die-cast alloy with a low profile and rounded edges to fit most design applications. All components are prepainted or have plated surfaces to inhibit corrosion. Non-corroding screw terminals are provided for wire connections to the LE-HPS-SA-EX/WP.

The LE-HPS-SA-EX/WP has a white pull down lever in its center. Pulling down the lever latches it into place. The LE-HPS-SA-EX/WP's normally open contact switch is shorted causing an alarm on the fire initiating loop. The pull down lever can not be reset unless the correct key is inserted into the manual fire alarm box lock and the unit is opened. The latching lever can then be restored to its normal position.

When the LE-HPS-SA-EX/WP is being reset and has a glass break rod installed, all debris must be removed prior to installing another rod to ensure the unit will close and lock securely.



FEATURES

- Compatible with all Hochiki Control Panels
- Rugged die-cast housing
- Rated class I group B (hydrogen) C&D, class II groups E,F,G, class III, 4X outdoor
- Weather Proof
- Corrosion-resistant construction
- Latching alarm levers
- Screw Terminals 12-22 AWG
- Key-locked reset
- Optional glass break rod
- DPDT Contacts

SPECIFICATIONS

Contacts	DPDT Form "C" (NO/C/NC)
Contact Current Rating	10 Amps @ 120/240 VAC
Dimensions	(HxWxD) 4.75 in. x 3.125 in. x 3.375 in. (12.1 cm x 7.9 cm x 8.6 cm)



UL S24978